

EHD Components 2005 (Pty) Ltd

E-mail:

JHB: ehd@ehd.co.za
 CPT: ehdcapetown@ehd.co.za
 DBN: ehd.dbn@ehd.co.za
 BLOEM: ehdbloem@ehd.co.za

Contact Number:

JHB: +27 (0)11 870 5000
 CPT: +27 (0)21 510 0567
 DBN: +27 (0)31 700 1160
 BLOEM: +27 (0)51 430 5404

MG3000C/MG7500CL

MG3000C/MG7500CL

Model		MG3000CL	MG7500CL
Generator	AC Frequency (HZ)	50	50
	AC Output Voltage (V)	110;120;220;240;110/220;120/240	
	Rated AC Output (kw)	2.5	6.5
	DC Output	12V-8.3A	
	Rated Current	10.5A	27.3A
Engine	Engine Model	M200	M420
	Starting System	Recoil or Electric	
	Fuel Tank Capacity (L)/(US.Gal)	CL=15/3.96	25/6.5
	Oil Capacity (L)/(US.Gal)	0.6	1.4
	Rated Speed(rpm)	3000	3000
Unit	Dimensions (LxWxH)	590x430x460	685x485x550
	(mm) / (inch)	23.2x16.9x18.1	26.9x19x21.6
	Net Weight (kg)/(lbs)	44.5/97.9	97.5/214.9507

Characteristics:

1. Powered by MELLGA 4-Stroke OHV petrol Engine
2. Circuit breaker protects overload operation.
3. Large fuel tank ensures 8 hours of continuous running
4. AVR alternator provides stable voltage and current.
5. Emergency low oil alert warn the low lube oil level.

Disclaimer

Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers

Source: www.ehd.co.za