

# EHD Components 2005 (Pty) Ltd

**E-mail:**

JHB: ehd@ehd.co.za  
 CPT: ehdcapetown@ehd.co.za  
 DBN: ehd.dbn@ehd.co.za  
 BLOEM: ehdbloem@ehd.co.za

**Contact Number:**

JHB: +27 (0)11 870 5000  
 CPT: +27 (0)21 510 0567  
 DBN: +27 (0)31 700 1160  
 BLOEM: +27 (0)51 430 5404

Enclosed Diesel Generator

## Enclosed Diesel Generator

Model	MDG6000S
Frequency (Hz)	50
Max. AC output (kw)	5.0/5.5
Cont. AC output (kw)	4.2
Rated Current (A)	20.5
Voltage (V)	110;120;220;110/220;120/240
D.C. output (V-A)	12/8.3
Power Factor	1
Engine Model	MD186FG
Displacement (cc)/(cu.in)	418/25.5
Engine Speed (rpm)	3000/3600
Engine Starting System	Electric
Lube Oil Capacity (L)/(US.Gal)	1.65/0.44
Fuel Tank Capacity (L)/(US.Gal)	16/4.22
Operational Capacity (hr)	7.8
Dimensions (LxWxH)	900x520x700
(mm)/(inch)	36*21.2*29.1
Net Weight (kg)/(lbs)	150/330.693
Noise Level at 7 M (dBA)	70

**Characteristics:**

1. Minimal vibration & smooth running;
2. Double large efficient muffler & soundproof canopy lower noise to 70dBA at 7m;
3. 16L fuel tank ensures 7 hours of continuous running;
4. Easy to move with durable 4-wheel rolling structure.

**Specifications:**

## Disclaimer

Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers

**Source: [www.ehd.co.za](http://www.ehd.co.za)**