

EHD Components 2005 (Pty) Ltd

E-mail:

JHB: ehd@ehd.co.za
 CPT: ehdcapetown@ehd.co.za
 DBN: ehd.dbn@ehd.co.za
 BLOEM: ehdbloem@ehd.co.za

Contact Number:

JHB: +27 (0)11 870 5000
 CPT: +27 (0)21 510 0567
 DBN: +27 (0)31 700 1160
 BLOEM: +27 (0)51 430 5404

Enclosed Diesel Generator

Enclosed Diesel Generator

Model	MDG6000S
Frequency (Hz)	50
Max. AC output (kw)	5.0/5.5
Cont. AC output (kw)	4.2
Rated Current (A)	20.5
Voltage (V)	110;120;220;110/220;120/240
D.C. output (V-A)	12/8.3
Power Factor	1
Engine Model	MD186FG
Displacement (cc)/(cu.in)	418/25.5
Engine Speed (rpm)	3000/3600
Engine Starting System	Electric
Lube Oil Capacity (L)/(US.Gal)	1.65/0.44
Fuel Tank Capacity (L)/(US.Gal)	16/4.22
Operational Capacity (hr)	7.8
Dimensions (LxWxH)	900x520x700
(mm)/(inch)	36*21.2*29.1
Net Weight (kg)/(lbs)	150/330.693
Noise Level at 7 M (dBA)	70

Characteristics:

1. Minimal vibration & smooth running;
2. Double large efficient muffler & soundproof canopy lower noise to 70dBA at 7m;
3. 16L fuel tank ensures 7 hours of continuous running;
4. Easy to move with durable 4-wheel rolling structure.

Specifications:

Disclaimer

Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers

Source: www.ehd.co.za