

EHD Components 2005 (Pty) Ltd

E-mail:

JHB: ehd@ehd.co.za
 CPT: ehdcapetown@ehd.co.za
 DBN: ehd.dbn@ehd.co.za
 BLOEM: ehdbloem@ehd.co.za

Contact Number:

JHB: +27 (0)11 870 5000
 CPT: +27 (0)21 510 0567
 DBN: +27 (0)31 700 1160
 BLOEM: +27 (0)51 430 5404

High Speed Air Cooled Double Cylinder

High Speed Air Cooled Double Cylinder

DESCRIPTION	SKT-8	SKT-12	SKT-16	SKT-20	SKT-25
Rated Horse Power kw	5.9	8.8	11.8	14.7	18.4
(IS: Rating A) bhp	8	12	16	20	25
No. of Cylinder	Single	Single	Double	Double	Double
Rated Speed rpm	1500	1500	1500	1500	1500
Bore mm	95	114.3	95	102	114.3
Stroke mm	110	116	110	110	116
Fuel g/kw/h	250	250	250	250	250
Consumption g/bhp/h	184	184	184	184	184
Lub. Oil	Yantrol				
Lub. Oil Consumption Liter/hr	0.018	0.026	0.033	0.04	0.42
Fuel Tank Capacity Liter	9	12	12	12	12
Net Weight Kgs	185	206	280	305	310
Lbs	407	454	617	672	683
Approx. Quantity in 20' FCL	80	80	44	44	44
Measurement l x b x h(mm)	584 x 482 x 765	586 x 482 x 765	736 x 533 x 762	736 x 533 x 762	736 x 533 x 762

Disclaimer

Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers

Source: www.ehd.co.za