

EHD Components 2005 (Pty) Ltd

E-mail:

JHB: ehd@ehd.co.za
 CPT: ehdcapetown@ehd.co.za
 DBN: ehd.dbn@ehd.co.za
 BLOEM: ehdbloem@ehd.co.za

Contact Number:

JHB: +27 (0)11 870 5000
 CPT: +27 (0)21 510 0567
 DBN: +27 (0)31 700 1160
 BLOEM: +27 (0)51 430 5404

Silent Generator

Silent Generator

Specification	TP12000DG-A	TP12000DGS-A	TP9500DGS
Rated frequency(hz)	50hz	50hz	50hz
Rated Rotation Speed(rpm)	3000	3000	3000
Rated voltage(v)	220 or 380	220 or 380	220 or 380
Rated output(kw)	9	8	6.5
Max output(kw)	10	9.5	7.5
DC output(V.A)	12/8.3	12/8.3	12/8.3
Phase No.	Single phase or 3 phase	Single phase or 3 phase	Single phase or 3 phase
Structure type	Open flame type	Silent type	Silent type
Fuel Tank capacity(L)	25L	25L	
Noise Level@7m	74-80	72-74	72-74
Lube	Cdgrade or SAE 10W-30, 15W-40		
Fuel	0#(summer) or 10#(winter light(chillness) diesel oil		
Starting system	Electrical Start		
Diesel Engine Model	2V286 V-Twin, 4-stroke, air cooled		
Displacement(cc)	840	840	498
Fuel Consumption(L/h)	2.89	2.57	
Compression ratio	20:01	20:01	19:01
Battery Ah	12V 36Ah	12V 36Ah	12V 36Ah
Protection system	low oil alarm	low oil alarm	low oil alarm
Overall dimension(LxWxH)(mm)	1040x660x740	1120x720x900	950x570x770
Weight/kg	205	260	185

Disclaimer

Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers

Source: www.ehd.co.za