

# EHD Components 2005 (Pty) Ltd

**E-mail:**

JHB: ehd@ehd.co.za  
 CPT: ehdcapetown@ehd.co.za  
 DBN: ehd.dbn@ehd.co.za  
 BLOEM: ehdbloem@ehd.co.za

**Contact Number:**

JHB: +27 (0)11 870 5000  
 CPT: +27 (0)21 510 0567  
 DBN: +27 (0)31 700 1160  
 BLOEM: +27 (0)51 430 5404

## Silent Generator

# Silent Generator

Specification	TP12000DG-A	TP12000DGS-A	TP9500DGS
Rated frequency(hz)	50hz	50hz	50hz
Rated Rotation Speed(rpm)	3000	3000	3000
Rated voltage(v)	220 or 380	220 or 380	220 or 380
Rated output(kw)	9	8	6.5
Max output(kw)	10	9.5	7.5
DC output(V.A)	12/8.3	12/8.3	12/8.3
Phase No.	Single phase or 3 phase	Single phase or 3 phase	Single phase or 3 phase
Structure type	Open flame type	Silent type	Silent type
Fuel Tank capacity(L)	25L	25L	
Noise Level@7m	74-80	72-74	72-74
Lube	Cdgrade or SAE 10W-30, 15W-40		
Fuel	0#(summer) or 10#(winter light(chillness) diesel oil		
Starting system	Electrical Start		
Diesel Engine Model	2V286 V-Twin, 4-stroke, air cooled		
Displacement(cc)	840	840	498
Fuel Consumption(L/h)	<b>2.89</b>	<b>2.57</b>	
Compression ratio	20:01	20:01	19:01
Battery Ah	12V 36Ah	12V 36Ah	12V 36Ah
Protection system	low oil alarm	low oil alarm	low oil alarm
Overall dimension(LxWxH)(mm)	1040x660x740	1120x720x900	950x570x770
Weight/kg	205	260	185

## Disclaimer

Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers

**Source: [www.ehd.co.za](http://www.ehd.co.za)**